

Work tables

Electric stands



Connect electric stand 376 in chrome, tabletop with bevelled edge in white laminate

A high quality of electronics and mechanics is determinant for reliability, durability and function with regard to desks with electric stands. Our seat & stand tables are built for daily use in rough conditions. You will notice the form of an extra high stability and low noise level.

If you need service in the future, you can feel secure as to the fact that the stands are marked with a serial number and they are also component built. It is to localize the faults, and if necessary to change the components. The tables have an integrated range of accessories for the connections of computers, lighting, cable management etc.

Our electric stands is available as two or three column stands and and they are (with the exception of Duo 379) eco-labelled with the Swan.



Connect CT3 round design

Connect electric stand 376 CT3 in white lacquer with tabletop ECP (profile 4).

Contur rectangular design

Contur electric stand 394 in silver, tabletop in oak with bevelled edge (profile 1).



Flexiframe

All electric stands except 383 is equipped with Flexiframe function. This means that the stand is adjustable in width and thus adaptable for table tops in various sizes. An advantage is also that you can customize the width of the stand to the table top when mounting PC brackets, etc.



Sliding table top

The 2-column stands 394, 383 and 376 can be supplemented with a sliding table top, which means that the table top can be pushed backwards so that you can easily access the cables and connectors. Consoles for sliding table top are to be ordered separately. If the table screen and cable tray shall be mounted on the table with sliding top, special attachments for this are to be ordered separately.



Standard controller



Controller inset in the tabletop



Controller with display

Controller

As standard, all electric stands are delivered with a single controller, which is assembled under the table top. There is an additional controller with display that shows the height.

The controller with display, recessed in the table top, is available as an additional option.

TECHNICAL SPECIFICATIONS

- All electric stands are equipped with electronic components (motors/transformers) that makes all threshold values considering to magnetic- and electrical fields.
- Edsbyn's Sitt & stå tables have been tested and approved by the Swedish National Testing- and Research Institute according to the Furniture Facts requirement specification for stability, strength and safety.
- Stands with "friction lacquer" means that the stands stay looking good and free from scratching even after a long time of use.
- Tolerance adjusted slide parts give high stability and durability.
- Strong motors with some extra capacity means that the electric stands will make more than the stated maximum load 125 kg.
- Height adjustment with soft start/stop, low sound level and regular speed up/down.
- Serial numbers labeled and component constructed so that they will be easy to troubleshoot and if necessary to replace components.

Other variants of stands can be offered.

Electric stands Assortment



Duo 379 / 2 column

Our simplest electric stand. Not swan marked. Beamless with flexi-frame function. Lift capacity 100 kg incl tabletop. Available in two different height intervals 2D 70-120 cm and 3D 62-128 cm (includes tabletop).

flexi frame 1040 <||> 1680

Contur- rectangular shape □

905 ■
1305 ■
1605 ■



Contur-el 383 / 2 column

Stand in silver. Heights are including tabletop. The table can evenly be loaded with approx. 100 kg (including the weight of the tabletop), max 35 kg on the table ends. Height adjustment with pushbutton operation up and down.



Contur-el 383 / 3 column

Stand in silver. Heights are including tabletop. The table can evenly be loaded with approx. 100 kg (including the weight of the tabletop), max 35 kg on the table ends. Height adjustment with pushbutton operation up and down. The stand is 1605 mm (central stand, part with beam) and 1680 mm side stand.

As an option on stand 383 are different types of push buttons and sliding tabletop (see previous page)



Contur-el 394 / 2 column

Beamless 2 column stand with one motor in each leg. Pushbutton operation up and down. Lift capacity 125 kg evenly loaded. Flexiframe.

flexi frame 1040 <||> 1680



Contur-el 395 / 3 column

Same as 394.

flexi frame 1040 <||> 1680
1441 <||> 2081

As an option on stand 394 and 395 are different types of push buttons and sliding tabletop on stand 394 (see previous page)

Connect CT3- round shape ○



Connect-el 376 / 2 column

Beamless flexi-frame stand. Available in two different heights 2D 70-120 cm and 3D 63-128 cm (includes tabletop). Lift capacity 100 kg evenly loaded, max 35 kg in the table ends. Height adjustment with push button.

flexi frame 1040 <||> 1680



Connect-el 381 / 3 column

Same as 376.

flexi frame 1040 <||> 1680
1441 <||> 2081

As an option on stand 376 and 381 are different types of push buttons and sliding tabletop on stand 376 (see previous page)



Electric stands

Electric stand Duo 379

Contur-electric stand 383 / 2 pelare

Contur-electric stand 383 / 3 pelare

Contur-electric stand 394 / 2 pelare

Contur-electric stand 395 / 3 pelare

Connect- electric stand 376 CT3 / 2-pelare

Connect- electric stand 381 CT3 / 3-pelare

Sliding tabletop (383/394/376)

Extra cost

Stand in silver

Stand 905 mm silver

Stand 1305 mm silver

Stand 1605 mm silver

Stand 1605x1680 mm silver

Stand silver alt black

Stand chrome

Stand w hite lacquer

Stand silver alt black

Stand chrome

Stand w hite lacquer

Silver alt black

Stand chrome

Stand w hite lacquer

Silver alt black

Stand chrome

Stand w hite lacquer

Consoles for sliding tabletop

Fittings (2 p.) for table screen 548 & 582 / cable tray

Fittings (2 p.) for table screen 523 & 583 / cable tray , alt without cable tray

Cable tray Flexi

Pushbutton operation with display

Display inset in the tabletop

Skivor Typ 2 kan även erhållas spegelvända - Typ 1.

Typ 1 Typ 2

Höjd inkl skiva

| Family | Product | 2 part stand H.70-120 cm | | 3 art stand H. 62-128 cm | |
|--------|---------|-----------------------------|---|-----------------------------|---|
| | | Art | € | Art | € |
| | | 08 379 40203E | | 40207E | |
| | | 08 383 40201E | | 40205E | |
| | | 08 383 40202E | | 40206E | |
| | | 08 383 40203E | | 40207E | |
| | | 08 383 40303E | | 40307E | |
| | | 08 394 x 0203E | | x 0207E | |
| | | 08 394 10203E | | 10207E | |
| | | 08 394 60203E | | 60207E | |
| | | 08 395 x 0303E | | x 0307E | |
| | | 08 395 10303E | | 10307E | |
| | | 08 395 60303E | | 60307E | |
| | | 08 376 x 0053E | | x 0057E | |
| | | 08 376 10053E | | 10057E | |
| | | 08 376 60053E | | 60057E | |
| | | 08 381 x 3053E | | x 3057E | |
| | | 08 381 13053E | | 13057E | |
| | | 08 381 63053E | | 63057E | |
| | | 09 670 40100 | | | |
| | | 09 670 40200 | | | |
| | | 09 670 40300 | | | |
| | | 09 670 40000 | | | |



Replace x in the Art no (position 1) as following to choose colour of the stand:

4 = silver lacquer
7 = black lacquer

For pushbutton operation with display, state DISPLAY in plain language.